Università degli Studi di Padova

Padua Research Archive - Institutional Repository

Sustainability of using vineyard pruning residues as an energy source: Combustion performances and environmental impact

Original Citation:

Availability:

This version is available at: 11577/3287900 since: 2019-02-07T21:40:02Z

Publisher:

Published version:

DOI: 10.1016/j.fuel.2019.01.128

Terms of use:

Open Access

This article is made available under terms and conditions applicable to Open Access Guidelines, as described at <http://www.unipd.it/download/file/fid/55401> (Italian only)

(Article begins on next page)

Sustainability of using vineyard pruning residues as an energy source: combustion performances and environmental impact

Chiara Giorio^{1,*}, Sarah Pizzini², Enrico Marchiori³, Rossano Piazza^{2,3}, Stefano Grigolato⁴, Michela Zanetti⁴, Raffaele Cavalli⁴, Marco Simoncin⁵, Lidia Soldà¹, Denis Badocco¹, and Andrea Tapparo¹

¹ Department of Chemical Sciences, University of Padova, Via Marzolo, 1 - 35131 Padova, Italy

² Institute for the Dynamics of Environmental Processes, National Research Council (CNR-IDPA), Via Torino, 155 - 30172 Venice Mestre (VE), Italy

³ Department of Environmental Sciences, Informatics and Statistics, Ca' Foscari University of Venice, Via Torino, 155 - 30172 Venice Mestre (VE), Italy

⁴ Department of Land, Environment, Agriculture and Forestry, University of Padova, Via dell'Università, 16 - 35020 Legnaro, Padova, Italy

⁵ Uniconfort Srl, Via dell'Industria, 21 - 35018 San Martino di Lupari, Padova, Italy

* Correspondence to: chiara.giorio@unipd.it

Abstract

Open burning of agricultural waste is still a common practice as it is a rapid method for waste disposal, although natural biomass, including agriculture residues, can be exploited as a renewable energy source. We assessed the viability and sustainability of using vineyard pruning residues, as wood chips, for energy conversion. Wood chips, obtained from vineyards in the Prosecco DOCG region (Italy), were characterized in terms of chemical composition, calorific value, ash content and humidity. Combustion tests were performed in a medium-size biomass boiler (maximum power 500 kW) to assess the viability of the approach in terms of sustainable steady-state combustion. Primary emissions of both macro- and micro-pollutants were measured to assess the environmental impact. An analytical method was purposely developed for the determination of polycyclic aromatic hydrocarbons (PAHs), polychlorinated biphenyls (PCBs), polychlorinated dibenzo-p-dioxins (PCDDs) and polychlorinated dibenzofurans (PCDFs) in three matrices: fly ashes, condensate and gas. The results showed that vineyard pruning residues can be used for energy conversion in

31 medium- and large-scale biomass boilers. Primary emissions of measured pollutants were all below
32 limit values set by current European legislation except for particulate matter, for which current
33 available abatement technologies are required to contain emissions, thus making the use of vineyard
34 pruning residues unsuitable for combustion in domestic appliances where such technologies are not
35 installed. Bottom ashes produced during combustion were also characterized to assess whether they
36 can be recycled in the vineyard as soil amendments/fertilizers. Copper content in combustion ashes
37 exceeded limit values for ashes to be used as fertilizers in agricultural fields for some European
38 countries but not for others, indicating that ashes may need to be disposed as waste.

39

40 **Keywords**

41 Waste-derived fuel, Biomass, Vineyard residues, Wood boiler, Emissions, Persistent organic
42 pollutants (POPs)

43 **1 Introduction**

44 The most recent scenarios depict a rise in world energy demand by 30% between today and 2040,
45 which is equivalent of adding another China and India to today's global demand [1]. It is therefore
46 imperative to shift towards renewable energy sources and increase energy efficiency in order to
47 limit global temperature rise and meet the goals set by the Paris climate agreement [2].

48 Natural biomass, including agriculture residues, is a renewable energy source [3], although this
49 definition does not consider the very different timescales when comparing carbon emissions during
50 burning and resequestration during a plant's lifetime [4]. Currently, a significant part of the energy
51 from agricultural by-products and wastes is lost: open burning is still a common practice as it is a
52 rapid method for waste disposal [5–7] but with considerable detrimental impacts on air quality
53 [8,9]. Besides the underestimated risk of fire, this practice not only causes uncontrolled release of
54 greenhouse gasses without recovering any energy, but it can be also the cause of uncontrolled
55 emissions of particulate matter (PM) and of persistent organic pollutants (POPs) in the
56 environment, such as polychlorinated dibenzo-p-dioxins and furans (PCDD/Fs),
57 polychlorobiphenyls (PCBs) and polycyclic aromatic hydrocarbons (PAHs) [7,10,11]. These
58 compounds are a cause of concern for human health and for the environment. Once emitted, these
59 POPs tend to accumulate in fatty tissues and in the food chain. They are also very persistent and
60 therefore subject to long-range atmospheric transport [12]. In fact, they have been detected even in
61 the most pristine environments on Earth [13].

62 Modern air quality regulations aim at reducing both intentional and unintentional release of micro-
63 pollutants in the environment. In this connection, open burning of agricultural residues has been
64 strictly limited or prohibited by local authorities (for instance in Italy since 2010 with the
65 Legislative Decree D.Lgs. 205/2010 [14]). Otherwise, the controlled burning of waste-derived
66 biomasses for energy use can be a viable and safer alternative [15] to uncontrolled burning in the
67 field. Anyway, the sustainability of this resource requires that other environmental aspects are
68 correctly addressed, in particular those regarding the management (collection, transport and

69 processing) of the biomass to be used as fuel, the atmospheric emissions during controlled burning,
70 and ash disposal.

71 In many countries, vineyard pruning residues (VPRs) represent a good example of agricultural
72 waste that can become fuel. Recent studies have investigated the possibility to exploit this available
73 biomass as an energy source, through the characterization of the biomass [16,17] and its use both as
74 wood chips [18] and as pellets [19,20] in domestic appliances. However, due to the high ash content
75 and humidity, maintaining an efficient steady-state combustion in domestic appliances has proven
76 to be challenging [18,19] and the use of larger scale biomass boilers has been suggested as a better
77 alternative [21].

78 In a densely inhabited area, the presence of large-scale thermal and power plants can be not well
79 accepted by local residents. This highlights a contradictory opinion, on one side biomass thermal or
80 power plants are considered fundamental to increase the share of renewable energy in the country,
81 on the other side large size plants, especially when low quality biofuel is used, face opposition by
82 local residents [22]. As a consequence, the type, location and operation of the facilities play a
83 fundamental role on the social acceptance [23]. Besides this, the northern Italian Po valley
84 represents a European hot-spot concerning aerosol pollution [24], where local authorities often limit
85 the use of wood burning appliances in winter [25]. It follows the need to evaluate the environmental
86 drawbacks of using biofuels derived from poor quality residual biomass, such as VPRs, in medium-
87 size boiler.

88 In this study, for the first time, we investigate the possibility of exploiting VPRs, as wood chips, for
89 energy conversion in a medium-size biomass boiler (maximum power 500 kW) taking into account
90 also the related environmental drawbacks. The study aims at assessing the viability and the
91 sustainability of the steady-state combustion of VPRs, as wood chips, in a medium-size biomass
92 boiler. The overall environmental impact of the combustion process is here evaluated in terms of
93 quality of the VPR wood chips as fuel, primary emissions of both macro- and micro-pollutants and
94 ashes produced from the combustion process.

95 **2 Materials and methods**

96 **2.1 Characterization of the VPRs**

97 The VPR wood chips were collected in a specific geographical area in northern Italy, the Prosecco
98 DOCG region, a hilly countryside area at the margin of the Po valley characterized by a significant
99 high density of vineyards. In the Prosecco DOCG district (6650 ha) the estimated production of
100 VPRs is of 25000 t/y. The sample used in this study was obtained by chipping VPRs using a
101 purpose-build shredder machine, the Cobra Collina® of Peruzzo S.r.l. (Curtarolo, Padova, Italy).
102 The main advantage in the use of purpose-build shredder machine lies in the versatility of the
103 machine and in the logistics of storage and handling that is better suited to the vineries in the area
104 even for limited storage spaces (the chipped VPRs occupy less space than the densified material
105 balers).

106 After harvesting, the wood chips were transported and stored in the proximity of the farm in
107 covered piles for a period of 7 months. Covering the VPRs with an impermeable and breathable
108 sheet has the advantage of accelerating the seasoning and preserving the quality of the material.
109 Furthermore, with heaps with a contained height and a wide base, the preservation of the material is
110 further encouraged. At the end of this period, the wood chips were transported in big-bags (volume
111 of 1000 liters each) to the experimental biomass boiler site. Once stored at the experimental site,
112 three samples of 50 liters of wood chips were collected and transported to the biofuel laboratory to
113 be characterized in terms of physico-mechanical properties by the determination of moisture
114 content, ash content, high heating value and particle size [19]. The three samples refer to the initial
115 characterization done after 7-month seasoning in a covered pile, just before the first combustion
116 test. While additional characterization tests over time were not done, it is expected that physical-
117 mechanical characteristics of the fuel had not changed significantly afterwards. The values of the
118 aforementioned parameters were assessed according with the recent in force ISO standards for solid
119 biofuel quality assessment [26]. The moisture content of the sample was measured following the

method described in the EN ISO 18134-1 [27]. Three samples were placed in a ventilated oven at 105±2°C for up to 24 hours until constant weight was attained. The ash content was measured according to the EN ISO 18122 [28], using three samples of grounded chips of minimum 1 g each. The samples were weighed before and after their complete combustion that was carried out according to the temperature program stated in the EN ISO 18122 [28]. The reported ash contents are the average of the three repeats on a wet basis (as received). To measure the high heating value of the samples as received (HHVar) an IKA® C-200 calorimeter was used (three repeats; IKA®-Werke GmbH & Co. KG). The high heating value on a dry basis and ash free (HHVdaf) is calculated as indicated in the standard EN ISO 18125 [29]. To measure the particle size distribution, a volume of 8 liters of the wood chips have been sieved at moisture content below 20 w-% on a wet basis to prevent the fine particles from sticking together or losing moisture during the sieving process. Five circular sieves (metal plates) with round perforated holes from 3.15 to 63 mm, in accordance with ISO 3310-2 [30], have been used for particle size determination following the ISO 17827-1 [31]. Since in the general requirement for solid biofuel EN ISO 17225-1:2014 [32] the VPRs are referred to as woody biomass and identified with origin number 1.1.7 “*Segregated wood from gardens, parks, roadside maintenance, vineyards, fruit orchards and driftwood from freshwater*”, the determination of particle size classes has been made in accordance with EN ISO 17225-4:2014 [33], where the origin 1.1.7 is a subset of the 1.1 “*Forest, plantation and other virgin wood*”, and it refers to a B quality class.

2.2 Combustion tests and measurements of gas and particulate emissions

Three combustion tests and measurement campaigns were done on the 9th August 2012, 21st December 2012 and 24th April 2013 for a duration of about 10 hours each. The combustion tests of the VPRs were carried out in a medium-size experimental biomass boiler (Uniconfort S.r.l., San Martino di Lupari, Padova, Italy), with a maximum power of 500 kW (Figure 1). The boiler is equipped with an automatic feeding system which slowly brings the wood chips to the furnace by

145 means of a movable grate. After the furnace, exhaust gases are transported to the post-combustion
 146 chamber where they enter into contact with the heat-exchange unit. Combustion parameters (*e.g.*,
 147 furnace temperature, post-combustion chamber temperature, flue gas temperature, % O₂ in the flue
 148 gas) are monitored and self-adjusted in continuous to ensure maximum efficiency (O₂ 11%).
 149 Combustion ashes are removed continuously from the grate through an automatic extractor.

Figure 1. Picture and schematic representation of the wood boiler.

153 During the campaigns, continuous measurements of the concentrations of O₂, CO₂, CO, NO_x, SO₂,
 154 C₃H₈, H₂S in the exhaust, together with combustion efficiency, combustion air temperature, and
 155 exhaust air temperature, were done using a MRU[®] VARIOplus (MRU Instruments, Inc.) at about
 156 2 m down the flue from the heat-exchange unit (fume temperature 160-200°C).

157 Total suspended particles (TSP) were measured following the method EN 13284-1 [34], at a height
 158 of about 6 m (duct diameter 35 cm, fume temperature about 160-200°C). Isokinetic conditions (flue
 159 gas velocity of 3-5 m s⁻¹) were maintained throughout the sampling (~5 minutes, 1-2 repetitions per
 160 experiment) by using nozzles with different internal diameters, monitoring the exhaust gas velocity
 161 in the duct and by manually adjusting the aspiration flow from the pump (ZB1 timer, Zambelli
 162 S.r.l., Milan, Italy). Filters used for TSP collection were made of quartz fiber (QFF, AQFA type,

Merck Millipore KGaA), and they were pre-treated at 400°C for 4 hours. Weighing of the filters was done, before and after sampling, after conditioning at a temperature of 20±1°C and relative humidity of 50±5% for at least 48 hours, as in previous studies [35]. The effect of weighing filters at 50% relative humidity rather than dry conditions is negligible in our experimental conditions because the hygroscopic growth factors at 50% relative humidity during hydration are small even for very hygroscopic particles like NaCl [36]. Flue gas velocity and volumetric flow were measured using the method UNI 10169 [37] in-between each sampling.

2.3 Determination of PAHs, PCBs and PCDD/Fs

2.3.1 Sampling

The sampling was carried out at a height of about 6 m (duct diameter 35 cm, fume temperature 160-200°C) in isokinetic regime using the “filter/condenser method” EN 1948-1 [38]. The sampler is composed of a glass probe inserted in a thermostated tube (120°C), a thermostated box (120°C) containing the filter holder fitted with a quartz fiber filter (QFF, AQFA type, Merck Millipore KGaA), a glass condenser maintained at 5°C using a chiller, a resin cartridge (~10 g of Amberlite® XAD®-2, Supelco® or XAD®-2 Ultra-Clean Resin, Restek Co.) at room temperature, and a constant flow pump. During sampling, gas velocity in the duct was continuously monitored using a Pitot tube. The isokinetic condition (flue gas velocity of 3-5 m s⁻¹) was maintained by using nozzles with different internal diameters and by manually regulating the aspiration flow throughout the sampling (~3 hours, 1-2 repetitions per experiment). This system allows the collection of three different fractions: in the first step, the PM was collected on QFFs, then the vapors were condensed and collected in a glass bottle placed under the condenser, and finally the gaseous products were adsorbed in the resin cartridge. The filters used for PM collection were pre-treated at 400°C for 4 hours and spiked with 4x100 µL of 4 ¹³C-labelled PCB standards at 20 pg µL⁻¹ (PCB SYRINGE SPIKE, PCB-70/111/138/170, 1000 ng mL⁻¹, CIL – Cambridge Isotope Laboratories, Inc., diluted 2:100 in iso-octane, >99.3%, ROMIL-SpS™) before sampling.

188 2.3.2 Extraction

189 Three different extraction procedures for the three different matrices (fly ash on the QFFs,
190 condensate, gas adsorbed on the resins) were used, following the indications of the method EN
191 1948-2 [39]. Nevertheless, in order to enhance repeatability and reduce contamination risks,
192 automated instruments were used for analytes extraction, while toluene was replaced with low-
193 boiling and less toxic extraction solvents in order to shorten the concentration step and avoid the
194 loss of the most volatile analytes (*e.g.*, PAHs; see Figure S1 in the Supplementary Material). All
195 solvents used were Super Purity Solvents (SpS™, Romil Ltd.). All the tools and glassware were
196 washed with an aqueous 2% (v/v) Contrad® 2000 solution, dried with acetone and rinsed three
197 times with dichloromethane and three times with *n*-hexane.

198 For greater clarity, the steps of the proposed analytical method are summarized in the flow chart in
199 Figure S2.

200 Prior to extraction, blanks and samples were spiked with a known amount of isotope-labelled
201 solution (3 ¹³C-labelled PAHs at 1 ng μL⁻¹, 21 ¹³C-labelled PCBs at 40 pg μL⁻¹ and 15 ¹³C-labelled
202 PCDD/Fs at 10-20 pg μL⁻¹; CIL Inc.) as internal standards.

203 Concerning QFF samples, PAHs, PCBs and PCDD/Fs were extracted by means of a Pressurized
204 Liquid Extractor (PLE™ system, FMS, Fluid Management System Inc.) equipped with stainless
205 steel extraction cells, using *n*-hexane/dichloromethane (1:1, v/v). QFFs were broken in small pieces
206 and mixed with anhydrous sodium sulfate, diatomaceous earth and Ottawa sand (Sigma-Aldrich
207 Co., Applied Separation Inc.). The operative conditions were previously optimized for enhanced
208 extraction efficiency and to minimize the amount of solvent required [40,41]. The extractions were
209 performed at 100°C and 100 bar, with 3 static cycles of 7 min each. An acid pre-treatment, before
210 extraction, is often done for analysis of organic compounds in fly ashes [42]. The attack with acid is
211 carried out to disrupt the mineral conglomerates that are formed in the combustion process. These
212 conglomerates (solid sphere, cenosphere, solid unshaped carbon particles) are formed at high
213 temperature (1400°C) and are composed of Fe (Fe₂O₃), Al (Al₂O₃), Si (SiO₂), along with Ca, K, and

214 Mg [43–45]. The temperature reached in biomass boilers are much lower (in this work 500-700°C),
215 for these reasons the acid pretreatment was not performed in this study.

216 The condensate was extracted through a liquid-liquid extraction. The samples (about 70-100 mL)
217 were put in a separating funnel with 10 mL of dichloromethane. The funnel was shaken for 15
218 minutes and the organic phase was collected in a glass bottle. The extraction was repeated three
219 times in total. The three aliquots of organic phase were then combined and anhydriified with sodium
220 sulfate ($\geq 99.0\%$, anhydrous, ACS reagent, Sigma-Aldrich®). The procedural blank was prepared as
221 follow. A fourth aliquot of organic phase was used for extraction from the same sample and
222 disposed. Successively, the sample was spiked again with ^{13}C -labelled internal standards and the
223 extraction procedure was repeated another three times. The three aliquots of organic phase,
224 constituting the procedural blank, were then combined and anhydriified.

225 The volatile compounds adsorbed onto the XAD®-2 resin were extracted using Accelerated Solvent
226 Extraction (ASE™ 200, Thermo Scientific, Dionex, Inc.). The resin samples were extracted using
227 *n*-hexane/acetone (1:1, v/v) at a temperature of 100°C and a pressure of 120 bar using the procedure
228 optimized by Yang *et al.* [46]. The extraction procedure, 5 minutes static extraction after a 5 min
229 equilibration time, was repeated three times. After extraction, the cell was rinsed with the extraction
230 solvent and flushed with N₂. The total extraction volume was about 70 mL. The same extraction
231 procedure was also done on blank resin samples.

232 2.3.3 Clean-up

233 The clean-up procedure is the same for all extracts of the three matrices. The extracts were reduced
234 to a volume of 500 μL under a gentle 5.0 (99.999%) nitrogen flow at 23°C (Turbovap® II, Caliper
235 Life Science Inc.), recovered with 5 mL of *n*-hexane, and reduced again to 500 μL in the same
236 conditions. Purification was performed by directly injecting the sample into a disposable neutral
237 silica column in an automated system (Power-Prep™, FMS Inc.) and by eluting it with 30 mL of *n*-
238 hexane and 30 mL of *n*-hexane/dichloromethane (1:1, v/v). The eluates were collected as one single

fraction. Purified samples were reduced to 100 μL under a gentle nitrogen flow at 23°C and spiked with a known amount of the recovery standard solution (1 ^{13}C -labelled PAHs at 1 ng μL^{-1} , 2 ^{13}C -labelled PCBs at 40 pg μL^{-1} and 2 ^{13}C -labelled PCDD/Fs at 20 pg μL^{-1} ; CIL Inc.) according to the method fully described in Pizzini *et al.* [41,47].

2.3.4 Instrumental analysis

According to the method EN 1948-3 [48], analyses were performed by High-Resolution Gas Chromatography coupled both with Low and High-Resolution Mass Spectrometry (HRGC/LRMS and HRGC/HRMS respectively), while quantification was performed using internal standards and the isotopic dilution technique, using perfluorotributylamine (PFTBA; Sigma-Aldrich Co.) as the reference compound. 16 priority PAHs, 127 out of 209 possible PCB congeners and 17 2,3,7,8-substituted PCDD/Fs were investigated. All the results were corrected using the instrumental response factor and for the procedural blanks.

Instrumental determination of PAHs and PCBs was carried out using a HRGC/LRMS (Agilent 7890A Series GC System, coupled with an Agilent 5975 inert Mass Selective Detector, Agilent Technologies Inc.) operating in electron impact mode (EI, 70 eV). Acquisition was performed in selected ion monitoring (SIM) mode.

PCDDs and PCDFs were determined using a HRGC (Hewlett Packard - Agilent 6890 Series GC System, Agilent Technologies Inc.) coupled with a HRMS (Thermo Finnigan MAT 95XP, Thermo Fisher Scientific Inc.) operating in electron impact mode (EI, 45 eV, with $R \geq 10\,000$). Acquisition was performed using multiple ion detection (MID). Experiments were carried out monitoring the two most intense peaks of the EI spectra for each analyte.

Both instruments were equipped with a 60 m HP5-MS column (0.25 mm I.D., 0.25 μm film thickness, Agilent Technologies Inc.).

Operating conditions, reference and target ion masses are presented in detail in Tables S1-S6.

263 2.3.5 Data quality for the analysis of organic contaminants

264 Analytical bias and precision were estimated by analyzing different Standard Reference Materials
265 (SRMs) as similar as possible to the matrices under investigation. The instrumental detection limits
266 (IDLs) were evaluated as three times the standard deviation of the blank signal and ranged between
267 0.2 and 15 pg for PAHs, 0.2 and 6 pg for PCBs and 0.1 and 0.3 pg for PCDD/Fs (as injected
268 amounts). Since preliminary tests on real samples showed that concentrations of PCDD/Fs were
269 always below IDL, the analytical method for these classes of compounds was not validated further
270 and following discussion refers to PAHs and PCBs only.

271 Initial tests on the QFFs were done on *Fly Ash Reference Material* EDF-5369 (CIL Inc.), which
272 derives from the filter of a municipal waste incinerator in northern Italy. Nevertheless, this kind of
273 matrix contains high levels of cenospheres, requiring an acid pretreatment that breaks up these
274 conglomerates before the analysis. In order to be more consistent with the analytical protocol used
275 in this work, it was therefore decided to use SRM 1649B (*Urban Dust*) from NIST (National
276 Institute of Standard and Technology) to check the analytical quality of the method. Indeed, this
277 SRM has a micro- and macroscopic structure more similar to the real samples, even if it does not
278 come from direct combustion sources.

279 About 0.05 g of SRM were deposited on a QFF and analyzed for PAHs and PCBs as previously
280 described. Precision, measured as relative standard deviation (RSD) of three replicated analyses of
281 the same SRM, ranged from 0.2 to 12% for PCBs, with an average value of 2%. As for PAHs,
282 precision for single compounds ranged from 1 to 17% for high molecular weight (4-6 rings)
283 compounds, while for low molecular weight (2-3 rings) PAHs, RSD were 33% (with a total average
284 value of 12%). This high variability can be explained by their greater volatility and, hence,
285 sensitivity to the two steps of volume reduction that are required by the pre-analytical procedure.
286 The accuracy tests led to good results, with a relative error (E_R) in the range of 1-23% for PCBs,
287 while more than 60% of the certified analytes were accurate within 2σ for PAHs.

288 Concerning condensate, since there is no available SRM for this matrix, it was necessary to spike
289 tap water, previously extracted according to the method described, with a known amount of the
290 surrogate standard solution of each class of analytes. About 100 mL of spiked water were analyzed
291 for PAHs and PCBs. Three repetitions were executed. The precision, expressed as repeatability,
292 ranges between 4 and 10% for PCBs, with an average value of 6%. As for the PAHs, RSD ranges
293 between 2 and 21%, with an average value of 9%. The results for most of the PCB target
294 compounds were in good agreement with the certified/reference values, with the E_R in the range of
295 1-19%, while for PAHs E_R ranges from 1 to 44%, with the exception of Benzo[ghi]perylene,
296 systematically underestimated.

297 Concerning resin samples, in absence of a SRM to verify accuracy and precision of the analytical
298 procedure, a blank XAD[®] resin was spiked with a known amount of the surrogate standard solution
299 of each class of analytes and analyzed as described. Nevertheless, these kinds of resins contain high
300 background levels of PCBs causing an interference in the analysis. Therefore, the method was not
301 validated for this type of matrix and the concentration values obtained from its analyses are to be
302 considered as indicative values.

303 **2.4 Analysis of combustion ashes**

304 Combustion ashes were collected at the end of each test and analyzed according to the procedure
305 already described elsewhere [19,49]. Briefly, 0.3 g of ashes were treated with 3 g of nitric acid
306 (69%, PROLABO S.r.l., Milan, Italy) in a CEM Discover SP-D (CEM Corp., Matthews, NC, USA)
307 microwave digester, with a temperature ramp from 20°C to 200°C at 30 bar in 4 min, and
308 maintained at the final conditions for 2 min. After digestion, solutions were diluted in a 50 mL
309 volumetric flask with ultrapure water, produced by a Millipore Plus System (Milan, Italy, resistivity
310 18.2 M Ω cm⁻¹), and analyzed by ICP-MS (Agilent 7700x; Agilent Technologies, Santa Clara, CA,
311 USA).

3 Results and discussion

3.1 VPR wood chips quality

Physico-mechanical characteristics of the VPR wood chips are reported in Table 1. The moisture content (MC), the calorific values (HHV_{daf} and HHV_{ar}) and the granulometric classifications satisfy the requirement described in the EN ISO 17225-4:2014 [33] for type B wood chip samples but also for A1 and A2 classes. In fact the MC of the three wood chip samples, obtained thanks to the covering of the pile of VPRs with a breathable paper for 7 months, is $\leq 15\%$ (see “*Table 2 — Specification of graded wood chips*” of the EN ISO [33]), the calorific value of the wood chips is not set by the standard (as minimum value to be stated), while the particle size distribution P31S with 3.8% of fine fraction content is one of the classes included in the “*Table 1 — Particle size of graded wood chips*” of the EN ISO standard [33]. Even if all of the above classification parameters corresponded to the requirements for a class A graded wood chips, VPRs cannot be qualified as type A due to their origin (not included in the list of those allowed for a type A samples) and their ash content that is $> 3\%$ (Table 1), the limit set in the EN ISO standard [33] for type B wood chips. Due to their ash content, VPRs cannot be burned in domestic appliances. In any case, previous studies showed that maintaining an efficient steady-state combustion in domestic appliances is challenging with VPRs both as wood chips and pellets [18,19]. Indeed, as demonstrated in a previous study on the combustion of VPR pellets in a domestic stove, the high amount of ashes produced during combustion can compromise the combustion itself because burning VPRs requires a larger amount of injected air which in turn means a colder combustion chamber and higher pollutant emissions [19].

334 **Table 1. Average values (and standard deviations) of the physico-mechanical characteristics of chips from**
335 **vineyard pruning residues (VPRs) according to in force standards (MC: Moisture Content; HHVdaf: High**
336 **Heating Value on a dry basis and ash free; HHVar: High Heating Value as received; A: Ash content; P: particle**
337 **size distribution; F: fine fraction). The three samples were collected from a covered pile after 7-month seasoning,**
338 **before the first combustion test.**

Wood chips Sample #	MC (%)	HHVdaf (MJ kg ⁻¹)	HHVar (MJ kg ⁻¹)	A (%)	P class
1	11.7 (0.04)	18.07 (0.04)	17.57 (0.04)	3.10 (0.09)	P31S (F: 3.8%)
2	11.5 (0.03)	18.04 (0.04)	17.59 (0.03)	3.07 (0.15)	
3	11.6 (0.07)	18.01 (0.01)	17.58 (0.01)	3.08 (0.03)	

339
340 Furthermore, the concentrations of metals measured in the ashes (Table 2) produced during the
341 combustion tests showed a very high amount of Cu, 274±72 mg kg⁻¹, above the limit value of 10
342 mg kg⁻¹ for combustion in domestic appliances [33]. In addition to Cu, other elements such as As,
343 Cr, Ni, Zn far exceed the limits imposed by the legislation for use in household appliances [33].
344 Nevertheless, large scale combustion facilities are equipped with abatement technologies for fly
345 ashes, like cyclones [50] or bag house filters [51], and so, for this reason, the high metal content
346 would not necessarily constitute a problem for atmospheric emissions. Concerning the possibility of
347 re-using bottom ashes as soil amendments, in Italy there are not guidelines for the application of
348 biomass ashes on agricultural fields. For this reason, trace element content has been compared with
349 limits set in other European countries [52–54], such as Austria, Germany, Denmark, Sweden, and
350 Finland (Table 2). For all elements, concentrations in VPR ashes were below all limits set by the
351 aforementioned countries with the exception of Cu for which the amount exceeded limit values of
352 some countries, namely Germany and Austria, but not others. Therefore, combustion ashes may
353 need to be disposed as waste rather than be re-utilized in the agricultural fields as fertilizer.

354

355 **Table 2. Measured concentrations (and standard deviations) of metals in the ashes collected from the wood**
356 **boilers at the end of each experiment and range of limit values set in different European countries by current**
357 **legislation (where available) for re-use of ashes as fertilizers in agricultural fields.**

Measured concentrations	Range of limit values
-------------------------	-----------------------

	(standard deviations) (mg kg ⁻¹)	in EU countries ^a (mg kg ⁻¹)
Fe	15.1 (4.7) ·10 ³	
Al	8.3 (2.6) ·10 ³	
Mn	1000 (22)	
Cu	274 (72)	70-600
Zn	130 (70)	1000-7000
Cr	34.7 (8.7)	100-300
Ni	24.4 (5.7)	30-100
V	22.0 (8.2)	70-100
Pb	5.9 (1.1)	100-300
Co	4.9 (1.7)	
As	4.7 (1.9)	20-40
Mo	2.60 (0.87)	
Sn	1.22 (0.60)	
Cd	0.060 (0.068)	1.5-8
W	0.08 (0.10)	

^a Range of limit values in Germany, Austria, Denmark, Sweden and Finland for ashes to be re-used in agricultural soils.

3.2 Combustion tests and characterization of the emissions

While VPRs cannot be burned in domestic appliances, combustion tests performed in this study showed that VPRs can be used as an energy source in medium-size wood boilers (experimental boiler used had a maximum power 500 kW). In normal operating conditions, with automatic control/adjustment of combustion parameters, the combustion was stable throughout the entire duration of the experiments (up to 10 h). Typical conditions were characterized by a combustion chamber temperature of 500-750°C, exhaust gas temperature (after the heat-exchange unit) of 180-240°C, O₂ and CO₂ concentrations in the exhaust gas of 12-13% and 8-9%, respectively, providing a combustion efficiency of 86-89% with 12-20 kg h⁻¹ of fuel consumption (Figure 2).

Figure 2. Evolution of the concentrations of macro-pollutants, air and fume temperatures during the combustion test performed on the 21st December 2012 as an example of typical boiler running conditions. Dashed red squares indicates a period of low-energy demand triggering a stand-by phase of the boiler and the shut-down period.

Concerning macro-pollutants, their concentrations in the exhaust air were well below limit values of current legislation (Italian Legislative Decree, D.Lgs. 152/2006 [55] and EU standards for machineries [56]) for most of them, especially NO_x due to relatively low temperatures in the combustion chamber, and SO_2 due to low S content in the fuel (Table 3). CO concentrations were well below the limit values for most of the duration of the tests (steady-state phase). CO concentrations increased significantly only in non-optimal combustion conditions encountered during start-up, shut-down and low energy demand phases (*e.g.*, the central heating system of the factory was switched-off, therefore not dissipating the energy produced and triggering a stand-by phase of the biomass boiler; Figure 2). Conversely, TSP concentrations were always above limit values (Table 3). It is worthwhile to notice that the experimental boiler used was not equipped with

emission abatement devices, which are indeed mandatory to use in commercial wood boilers of similar sizes. Therefore, the problem of particle emissions would be dramatic only for small size/domestic boilers in which such devices are not deployed. In any case, such small size/domestic appliances are not fit for purpose, as evidenced also in previous studies, because of difficulties in maintaining stable combustion conditions due to excessive production of fly ashes with the fuel under study in both wood chip and pellet forms [18,19].

Compared with other types of woody biomasses, emissions of macro-pollutants were higher than emissions from combustion of beech as log woods in biomass boilers for CO (780 ± 410 vs. 15 mg MJ^{-1} for VPRs and beech, respectively), NO_x (650 ± 200 vs. 157 mg MJ^{-1} for VPRs and beech, respectively) and TSP (1200 ± 800 vs. 18 mg MJ^{-1} for VPRs and beech, respectively) but lower for SO₂ (2.6 ± 4.5 vs. 10 mg MJ^{-1} for VPRs and beech, respectively) [57]. Emissions of macro-pollutants were significantly higher than emissions from combustion of spruce in the form of wood chips (CO 75 mg MJ^{-1} , NO_x 127 mg MJ^{-1} , TSP 32 mg MJ^{-1}) and pellets (CO 17 mg MJ^{-1} , NO_x 81 mg MJ^{-1} , TSP 14 mg MJ^{-1}) except for SO₂ (2.6 ± 4.5 vs. 8 mg MJ^{-1} for VPRs as wood chips and spruce as pellets, respectively) [57].

398

Table 3. Average concentrations (and standard deviations) of macro-pollutants in the flue gas, compared with the limit values enforced in Italy, and emission factors (flue gas volumetric flow $700\text{-}1040 \text{ Nm}^3 \text{ h}^{-1}$) measured during the three measurement campaigns. LDL=Lower than Detection Limit.

	Concentrations in the flue gas (standard deviations)		Emission factors (standard deviations)			Limit values ^a
	mg Nm ⁻³	mg Nm ⁻³ O ₂ 11%	g h ⁻¹	g kg ⁻¹	g MJ ⁻¹	mg Nm ⁻³ O ₂ 11%
CO ^b	200 (100)	270 (150)	200 (100)	12.3 (6.5)	0.78 (0.41)	350
NO	143 (16)	184.3 (1.5)	169 (51)	10.3 (3.1)	0.65 (0.20)	
NO ₂	LDL ^c	LDL	LDL	LDL	LDL	
NO _x ^d	220 (24)	283.0 (3.0)	259 (78)	15.8 (4.8)	1.00 (0.30)	500
SO ₂	0.7 (1.2)	0.7 (1.2)	0.7 (1.2)	0.041 (0.071)	0.0026 (0.0045)	200
H ₂ S	LDL ^e	LDL	LDL	LDL	LDL	
C ₃ H ₈	71 (53)	95 (76)	76 (51)	4.6 (3.1)	0.29 (0.20)	
TSP ^f	330 (160)	450 (270)	310 (220)	19 (13)	1.2 (0.8)	100

^a Italian Legislative Decree D.Lgs. 152/2006 for boilers of $> 150 \text{ kW}$ and $\leq 3 \text{ MW}$, more restrictive than the EU

standards for boilers of ≤ 500 kW: CO 1200 mg Nm^{-3} , TSP 150 mg Nm^{-3} [56]; ^b Average of 2nd and 3rd experiments; ^c LDL (NO₂) = 5 ppm; ^d Calculated based on the molecular mass of NO₂; ^e LDL(H₂S) = 5 ppm; ^f Average of 1st and 2nd experiments.

402

403 **3.3 Emissions of micro-pollutants**

404 In the perspective of a sustainable management of vineyard practices, the environmental impact of
405 using VPRs as energy source needs to be evaluated. After estimating the performances of the
406 proposed analytical method, determination of PAHs, PCBs and PCDD/Fs was carried out on
407 samples coming from the three different combustion tests at the wood boiler (approximate sampling
408 volume of 1.5-3 Nm³). For each sample, three different matrices were collected: fly ash deposited
409 on QFFs, condensed and flue gas adsorbed on XAD[®] resins. The distribution pattern of the different
410 analytes was also investigated. Finally, quality standards and limits set by the Italian regulations
411 were used to verify if and when emissions exceeded limit values for emissions in the atmosphere
412 (Italian Legislative Decree, D.Lgs. 152/06 [55]), and the much more restrictive limit values for
413 emissions from waste incinerators (Italian Legislative Decree, D.Lgs. 46/2014 [58]).

414 The combustion tests have highlighted some critical issues that may arise when using VPRs for
415 energy conversion, especially concerning the difficulties in selecting and cleaning the material used
416 as fuel. Indeed, mixed together with the VPR wood chips, plastic residues were found deriving from
417 vineyard practices such as transport bags and shelters (plastic pipes for the protection of the base of
418 the vine). In the specific case of the study, it has been estimated that the plastic residues were below
419 0.5%. This fact may result in a supply of chlorine at high enough quantity to allow the occasional
420 formation of PCDD/Fs during combustion.

421 Measured PAH and PCB concentrations for each sampled matrix are reported in Table 4 as
422 averages and in Table S7 as single values for each experiment at the wood boiler. The most
423 abundant contaminants in the analyzed samples were, as expected, PAHs followed by PCBs.
424 Conversely, PCDD/Fs were always below detection limits.

425

426 **Table 4. Persistent Organic Pollutants (POPs) analyzed in three different combustion tests. Concentration levels**
427 **as averages (and standard deviations) of the three experiments for polycyclic aromatic hydrocarbons (PAHs; as**
428 **single compounds and total, ng Nm⁻³) and polychlorinated biphenyls (PCBs; as chlorination classes and total, pg**
429 **Nm⁻³) for each matrix analyzed. LDL = Lower than Detection Limit, n.a. = not analyzed.**

<i>POPs</i>		Concentrations in the flue gas (standard deviations)				Concentrations in the flue gas at O ₂ 11% (standard deviations)			
		<i>F</i> ^a	<i>C</i> ^b	<i>R</i> ^c	<i>Total</i>	<i>F</i>	<i>C</i>	<i>R</i>	<i>Total</i>
PAHs (ng Nm ⁻³)	Naphthalene	10.63 (0.84)	101 (65)	2010 (500)	2120 (520)	13.8 (1.7)	128 (80)	2630 (800)	2770 (810)
	Acenaphthylene	2.1 (1.8)	86 (88)	1060 (830)	1150 (920)	2.8 (2.3)	110 (120)	1400 (1100)	1500 (1200)
	Acenaphthene	0.35 (0.24)	2.0 (1.7)	4.7 (1.8)	7.1 (3.7)	0.44 (0.25)	2.4 (2.0)	6.0 (1.6)	8.8 (3.7)
	Fluorene	0.44 (0.20)	8.7 (8.3)	17.0 (5.5)	26 (14)	0.56 (0.22)	11 (11)	21.7 (6.3)	33 (17)
	Phenanthrene	17 (13)	440 (240)	780 (540)	1230 (730)	22 (17)	550 (290)	1020 (720)	1590 (960)
	Anthracene	1.74 (0.91)	24 (11)	45 (27)	71 (28)	2.2 (1.2)	30 (12)	59 (37)	91 (38)
	Fluoranthene	80 (110)	720 (600)	390 (590)	1200 (1300)	110 (150)	940 (790)	510 (770)	1600 (1700)
	Pyrene	130 (170)	1000 (1000)	530 (850)	1600 (2000)	170 (220)	1300 (1300)	700 (1100)	2200 (2600)
	Benz[a]anthracene	13.5 (8.1)	30.2 (4.1)	0.65 (0.73)	44 (12)	18 (11)	39.4 (8.9)	0.85 (0.95)	58 (20)
	Chrysene	34 (27)	85 (18)	2.0 (2.0)	121 (43)	46 (36)	110 (23)	2.6 (2.7)	158 (60)
	Benzo[b]fluoranthene	19 (18)	25 (17)	0.70 (0.64)	44 (35)	25 (23)	32 (22)	0.89 (0.84)	58 (46)
	Benzo[k]fluoranthene	4.8 (4.2)	11.4 (3.6)	0.113 (0.071)	16.3 (5.9)	6.3 (5.5)	15.0 (6.2)	0.145 (0.092)	21.5 (8.9)
	Benzo[a]pyrene	9.6 (5.3)	10.4 (5.8)	2.21 (0.56)	22 (11)	12.7 (7.2)	13.7 (7.8)	2.83 (0.48)	29 (15)
	Benzo[ghi]perylene	10.5 (6.6)	8.3 (6.5)	0.038 (0.066)	19 (11)	13.3 (8.4)	11.0 (8.7)	0.044 (0.076)	24 (14)
	Indeno[1,2,3-cd]pyrene	65 (72)	20 (16)	0.10 (0.17)	86 (88)	85 (95)	27 (22)	0.11 (0.20)	112 (115)
	Dibenz[a,h]anthracene	LDL	LDL	LDL	LDL	LDL	LDL	LDL	LDL
	Total (Σ ₁₆ PAHs)	400 (430)	2600 (2000)	4800 (3300)	7800 (5700)	530 (570)	3300 (2600)	6300 (4400)	10200 (7500)
PCBs (pg Nm ⁻³)	Cl-1	70 (120)	2200 (2800)	n.a.	2300 (2800)	90 (150)	2600 (3200)	n.a.	2700 (3100)
	Cl-2	300	3400	n.a.	3600	400	4100	n.a.	4500

		(470)	(3800)		(3700)	(620)	(4400)		(4300)
	Cl-3	210 (320)	2600 (2100)	n.a.	2800 (2300)	250 (370)	3200 (2500)	n.a.	3400 (2700)
	Cl-4	110 (140)	2800 (2900)	n.a.	3000 (3000)	150 (190)	3600 (3700)	n.a.	3800 (3900)
	Cl-5	53 (88)	4300 (3900)	n.a.	4300 (4000)	70 (120)	5400 (5100)	n.a.	5500 (5200)
	Cl-6	46 (79)	13000 (13000)	n.a.	13000 (13000)	60 (100)	17000 (17000)	n.a.	17000 (17000)
	Cl-7	90 (150)	9800 (8400)	n.a.	9800 (8500)	110 (190)	12000 (11000)	n.a.	12000 (11000)
	Cl-8	LDL	910 (640)	n.a.	910 (640)	LDL	1140 (800)	n.a.	1140 (800)
	Cl-9	0.53 (0.91)	LDL	n.a.	0.53 (0.91)	0.6 (1.1)	LDL	n.a.	0.6 (1.1)
	Cl-10	LDL	18 (17)	n.a.	18 (17)	LDL	22 (20)	n.a.	22 (20)
	Total (Σ ₁₂₇ PCBs)	880 (900)	39000 (32000)	n.a.	<u>40000</u> <u>(32000)</u>	1100 (1200)	49000 (40000)	n.a.	<u>50000</u> <u>(42000)</u>

^a Fly ash deposited on quartz fiber filters; ^b Condensate; ^c Flue gas adsorbed on XAD[®] resins.

3.3.1 PAHs

The detected concentrations of PAHs ranged widely, from 4.13 to 14.3 $\mu\text{g Nm}^{-3}$ as sum of all PAHs (with an average value of 7.81 $\mu\text{g Nm}^{-3}$). Nevertheless, the first two sampling campaigns showed a moderate variability, with a RSD of 13%. All the samples show a distinct pattern of PAH compounds in their distribution, generally enriched in Pyrene, Phenanthrene, Fluoranthene and Acenaphthylene. The predominant compound is Naphthalene, with values ranging from 1.62 to 2.66 $\mu\text{g Nm}^{-3}$ (with an average value of 2.12 $\mu\text{g Nm}^{-3}$), except for the third sampling campaign where other heavier compounds dominated (*i.e.* Pyrene and Fluoranthene). Dibenzo[a,h]anthracene was not detected in any of the samples, whereas Benzo[ghi]perylene and Indeno[1,2,3-cd]pyrene were detected only in the resin sample of the first sampling campaign.

As regards the estimation of carcinogenic potency and of degree of toxicity of these compounds, the analyzed samples present a pattern enriched of PAHs with a low value of Toxicity Equivalence Factor (TEF) [59]. Conversely, Benzo[a]pyrene and Dibenzo[a,h]anthracene, that are generally considered the most toxic and carcinogenic among the 16 U.S. Environmental Protection Agency

446 priority PAHs [60], showed levels of concentration respectively two order of magnitude lower
447 (from 12.9 to 33.7 ng Nm⁻³) or always below the IDL.

448 The distribution pattern of compounds in the three matrices was rather similar and unvaried, as
449 shown in Figure 3. The highest levels of PAHs were detected in resin samples (with an average
450 value of 4.84 µg Nm⁻³) and were mainly ascribable to Naphthalene and Acenaphthylene, which
451 jointly accounted on average for 70% of the total; slightly lower PAH concentrations were found in
452 condensate (with an average value of 2.57 µg Nm⁻³), while the values for fly ash samples were
453 comprised between 0.104 and 0.901 µg Nm⁻³ as sum of all PAHs.

454

455
456

Figure 3. Percentage distribution pattern of PAH compounds in the three matrices in analysis.

457

458 When each single compound is considered, the distribution pattern remains relatively constant and
459 showed a different matrix subdivision as the molecular weight of the analytes changes (Figure 4).

460 The lightest compounds (Naphthalene, Acenaphthylene, Acenaphthene, Fluorene, Phenanthrene and
461 Anthracene) are more volatile and, hence, they were adsorbed on the resin. Conversely, fly ash
462 deposited on QFFs were generally enriched in high molecular weight compounds (4 to 6 aromatic
463 rings). This is consistent with the physical-chemical properties of PAHs, in particular with the
464 decrease in vapor pressure with increasing molecular weight.

465

Figure 4. Average percentage distribution of concentration levels of single PAH compound analyzed in the three different matrices for each sampling campaign. NAPH: Naphthalene; ACNY: Acenaphthylene; ACN: Acenaphthene; FLU: Fluorene; PHE: Phenanthrene; ANT: Anthracene; FLT: Fluoranthene; PYR: Pyrene; BAA: Benz[a]anthracene; CRY: Chrysene; BBF: Benzo[b]fluoranthene; BKF: Benzo[k]fluoranthene; BAP: Benzo[a]pyrene; BPER: Benzo[ghi]perylene; IPYR: Indeno[1,2,3-cd]pyrene.

The detected concentrations are significantly lower than the threshold values indicated by the legislation for large combustion plants (0.1 mg Nm^{-3} for single compound, 150 mg Nm^{-3} for Naphthalene, Italian Legislative Decree, D.Lgs. 152/06 [55]), and for the more restrictive ones related to waste incinerators ($10 \text{ } \mu\text{g Nm}^{-3}$ as the sum of 11 compounds, Italian Legislative Decree, D.Lgs. 46/2014 [58]).

3.3.2 PCBs

Samples were analyzed for 127 of the 209 possible congeners of PCBs (namely for those related to the Aroclor commercial mixtures and the non-Aroclor PCB-11). Not all of them were found in all the samples analyzed: for instance, Octa- and Deca-chlorinated compounds were not detectable in any of the filter samples, while Nona-chlorinated compounds were always below the detection limits in condensates, as reported in Table 4. As previously explained, due to high background values of PCBs found in the commercial XAD[®] resin, it was not possible to determine the concentration of this class of analytes in the resin samples.

486 As reported for PAHs, the levels of concentration of PCBs ranged widely, from 4.91 to 68.8 ng Nm⁻³
487 ³ (average value of 40.1 ng Nm⁻³) with the second sampling campaign one order of magnitude lower
488 than the others. The congeners composition is enriched in compounds with a high degree of
489 chlorination: Hexa- and Hepta- represent, on average, 56% of the total distribution.
490 Also in this case, the distribution pattern of congeners in the two matrices under analysis is rather
491 constant. PCBs are preferentially distributed on the condensate (which represents 97.3-98.6% of the
492 PCB contamination), rather than on the filters where many homologue groups were below the
493 detection limits.
494 The obtained results are considerably lower than the threshold limit values for PCB emissions from
495 both large combustion plants (0.5 mg Nm⁻³, Italian Legislative Decree, D.Lgs. 152/06) and waste
496 incinerators (Italian Legislative Decree, D.Lgs. 46/2014).

497 3.3.3 PCDD/Fs

498 As anticipated, concentrations of PCDD/Fs were all below detection limits, therefore no particular
499 concern was evidenced. This fact could be ascribed to the low percentage of chlorine present in
500 VPR wood chips (about 8%). A further explanation may derive from insufficient sampling volumes
501 for the determination of compounds usually present at very low concentrations like PCDD/Fs.
502 Nevertheless, we have still done an evaluation of the potential overrun of the limits imposed by the
503 different legislations (10 µg Nm⁻³ for Italian Legislative Decree, D.Lgs. 152/06 and 0.1 ng Nm⁻³ for
504 Italian Legislative Decree, D.Lgs. 46/2014) comparing them with our highest instrumental detection
505 limit value (30 pg Nm⁻³) and using International Toxicity Equivalence Factors (I-TEFs) defined by
506 Van den Berg *et al.* [61]. Even our highest instrumental detection limit values are significantly
507 lower than the limits imposed by the Italian legislation, indicating that the use of VPRs as biofuel
508 does not present risks of POPs contamination.

509 **4 Conclusions**

510 In this study, we assessed the viability and sustainability of using VPRs, as wood chips, for energy
511 conversion. Wood chips from VPRs were characterized as fuel in terms of chemical composition,
512 calorific value, ash content and humidity. Results showed that VPRs comply with type B standards,
513 however due to high ash content they are not suitable for burning in domestic appliances.

514 Combustion tests were performed in a medium-size biomass boiler (maximum power 500 kW) to
515 assess the viability of the approach in terms of sustainable steady-state combustion. We found that
516 VPRs can be used successfully in medium-size boilers and the combustion was stable for all the
517 duration of the experiments (~10 h) with a combustion efficiency of 86-89%.

518 Primary emissions of both macro- and micro-pollutants were measured to assess the environmental
519 impact. Primary emissions of macro-pollutants, such as CO₂, CO, NO_x, and SO₂, were below limit
520 values of current European legislation except for PM emissions that were above the limits in all
521 combustion tests. It is worth noting that medium- and large-size biomass boilers need to be
522 equipped with abatement technologies for particle emissions, not used in this series of experiments,
523 therefore this potential environmental drawback would only be relevant for small-size domestic
524 appliances that cannot anyhow be used with this type of fuel. Concerning micro-pollutants, both
525 PAH and PCB concentrations in the particulate, condensate and volatile fractions collected from the
526 flue were well below limit values set for large scale biomass boilers and also for incinerators, for
527 which limits are much more restrictive. PCDD/Fs were always below detection limits of our method
528 and therefore combustion of VPRs does not pose risks for production of POPs.

529 Bottom ashes produced during combustion were also characterized to assess whether they can be
530 recycled in the vineyard as soil amendments/fertilizers. Heavy metal content was compared with
531 limit values set in other European countries as Italy does not have limit values for ashes distributed
532 in the field. All trace metals were below limit values except for copper, whose concentration
533 exceeded limit values for some countries but not for others, therefore bottom ashes may need to be
534 disposed as waste rather than used as soil amendments in agricultural fields.

535 The present study was based on a relatively homogeneous VPR sample with processing and storage
536 conditions that respect the local good practices. The use of wetter wood chips, wood chips with a
537 high percentage of fine particles or wood chips treated with chlorinated pesticides could influence
538 negatively the quality of emissions, especially in small- and medium-sized installations such as the
539 one used for this series of tests.

540 The analytical method developed for the determination of micro-pollutants, *i.e.* PAHs, PCBs and
541 PCDD/Fs, is fit-for-purpose to assess risks posed by emissions of compounds that are harmful for
542 public health. Further improvements of the analytical method may be done by testing the use of
543 polyurethane foam rather than XAD[®] resins for sampling the volatile components – because
544 background levels of PCBs in the XAD[®] resins were very high –, and by increasing sampling
545 volume to obtain a more accurate evaluation of PCDD/F concentrations.

546 While our study demonstrated the viability and sustainability of using VPRs for energy conversion,
547 more studies are needed to assess both the potential for aerosol formation in the atmosphere from
548 oxidation of emitted volatile organic compounds and whether additional abatement strategies would
549 be required.

550

551 **Acknowledgements**

552 This work was supported by the “PRO.S.E.C.CO” project (Italian acronym for Sustainable
553 Production of Energy from Combustion and of Compost – Rural Development Program (PSR)
554 2007-2013, Measure 124 – Veneto Region DGR 745 March 15, 2010). Combustion tests were
555 performed using the laboratory facilities of Uniconfort S.r.l.; authors are grateful to the R&D team
556 for their technical support during the experiments at the biomass boiler.

557

Declaration of competing interests

MS is an employee of Uniconfort S.r.l., producer of biomass boilers who fully collaborated in the present study. The producer did not provide funding for the research activity; had no role in the design of the study; in the collection, analyses or interpretation of data; in the writing of the manuscript, or in the decision to publish the results.

References

- [1] International Energy Agency (IEA). World Energy Outlook 2017: A world in transformation. 2017. <http://www.iea.org/weo2017/> (accessed June 27, 2018).
- [2] Rogelj J, den Elzen M, Höhne N, Fransen T, Fekete H, Winkler H, et al. Paris Agreement climate proposals need a boost to keep warming well below 2 °C. *Nature* 2016;534:631–9. doi:10.1038/nature18307.
- [3] Vassilev S V, Baxter D, Andersen LK, Vassileva CG. An overview of the chemical composition of biomass. *Fuel* 2010;89:913–33. doi:10.1016/j.fuel.2009.10.022.
- [4] Cornwall W. Is wood a green source of energy? Scientists are divided. *Science* (80-) 2017. doi:10.1126/science.aal0574.
- [5] Yevich R, Logan JA. An assessment of biofuel use and burning of agricultural waste in the developing world. *Global Biogeochem Cycles* 2003;17:n/a-n/a. doi:10.1029/2002GB001952.
- [6] Singh J, Singhal N, Singhal S, Sharma M, Agarwal S, Arora S. Environmental Implications of Rice and Wheat Stubble Burning in North-Western States of India. *Adv. Heal. Environ. Saf.*, Springer, Singapore; 2018, p. 47–55. doi:10.1007/978-981-10-7122-5_6.
- [7] Kim Oanh NT, Permadi DA, Hopke PK, Smith KR, Dong NP, Dang AN. Annual emissions of air toxics emitted from crop residue open burning in Southeast Asia over the period of

- 581 2010–2015. *Atmos Environ* 2018;187:163–73. doi:10.1016/J.ATMOSENV.2018.05.061.
- 582 [8] Lemieux PM, Lutes CC, Santoianni DA. Emissions of organic air toxics from open burning:
583 a comprehensive review. *Prog Energy Combust Sci* 2004;30:1–32.
584 doi:10.1016/j.pecs.2003.08.001.
- 585 [9] Estrellan CR, Iino F. Toxic emissions from open burning. *Chemosphere* 2010;80:193–207.
586 doi:10.1016/j.chemosphere.2010.03.057.
- 587 [10] Lohmann R, Breivik K, Dachs J, Muir D. Global fate of POPs: Current and future research
588 directions. *Environ Pollut* 2007;150:150–65. doi:10.1016/j.envpol.2007.06.051.
- 589 [11] Li X, Wang S, Duan L, Hao J, Li C, Chen Y, et al. Particulate and Trace Gas Emissions from
590 Open Burning of Wheat Straw and Corn Stover in China. *Environ Sci Technol*
591 2007;41:6052–8. doi:10.1021/es0705137.
- 592 [12] Lerche D, Van de Plassche E, Schwegler A, Balk F. Selecting chemical substances for the
593 UN-ECE POP Protocol. *Chemosphere* 2002;47:617–30. doi:10.1016/S0045-6535(02)00028-
594 0.
- 595 [13] Giorio C, Kehrwald N, Barbante C, Kalberer M, King ACF, Thomas ER, et al. Prospects for
596 reconstructing paleoenvironmental conditions from organic compounds in polar snow and
597 ice. *Quat Sci Rev* 2018;183:1–22. doi:10.1016/j.quascirev.2018.01.007.
- 598 [14] Italian Legislative Decree, D.Lgs. 205/2010, Implementation of the EU Directive
599 2008/98/EU n.d. <http://www.camera.it/parlam/leggi/deleghe/10205dl.htm> (accessed July 11,
600 2018).
- 601 [15] Kothari R, Tyagi VV, Pathak A. Waste-to-energy: A way from renewable energy sources to
602 sustainable development. *Renew Sustain Energy Rev* 2010;14:3164–70.

doi:10.1016/J.RSER.2010.05.005.

[16] Toscano G, Riva G, Duca D, Pedretti EF, Corinaldesi F, Rossini G. Analysis of the characteristics of the residues of the wine production chain finalized to their industrial and energy recovery. *Biomass and Bioenergy* 2013;55:260–7. doi:10.1016/j.biombioe.2013.02.015.

[17] Duca D, Toscano G, Pizzi A, Rossini G, Fabrizi S, Lucesoli G, et al. Evaluation of the characteristics of vineyard pruning residues for energy applications: effect of different copper-based treatments. *J Agric Eng* 2016;47:22. doi:10.4081/jae.2016.497.

[18] Picchi G, Silvestri S, Cristoforetti A. Vineyard residues as a fuel for domestic boilers in Trento Province (Italy): Comparison to wood chips and means of polluting emissions control. *Fuel* 2013;113:43–9. doi:10.1016/j.fuel.2013.05.058.

[19] Zanetti M, Brandelet B, Marini D, Sgarbossa A, Giorio C, Badocco D, et al. Vineyard pruning residues pellets for use in domestic appliances: a quality assessment according to the EN ISO 17225. *J Agric Eng* 2017;48:99–108. doi:10.4081/jae.2017.612.

[20] Giungato P, Barbieri P, Cozzutto S, Licen S. Sustainable domestic burning of residual biomasses from the Friuli Venezia Giulia region. *J Clean Prod* 2018;172:3841–50. doi:10.1016/j.jclepro.2017.05.190.

[21] Spinelli R, Nati C, Pari L, Mescalchin E, Magagnotti N. Production and quality of biomass fuels from mechanized collection and processing of vineyard pruning residues. *Appl Energy* 2012;89:374–9. doi:10.1016/j.apenergy.2011.07.049.

[22] Ribeiro F, Ferreira P, Araújo M, Braga AC. Public opinion on renewable energy technologies in Portugal. *Energy* 2014;69:39–50. doi:10.1016/j.energy.2013.10.074.

- 625 [23] Botelho A, Pinto LMC, Lourenço-Gomes L, Valente M, Sousa S. Social sustainability of
626 renewable energy sources in electricity production: An application of the contingent
627 valuation method. *Sustain Cities Soc* 2016;26:429–37. doi:10.1016/j.scs.2016.05.011.
- 628 [24] Bigi A, Ghermandi G. Trends and variability of atmospheric PM_{2.5} and PM_{10-2.5}
629 concentration in the Po Valley, Italy. *Atmos Chem Phys* 2016;16:15777–88.
630 doi:10.5194/acp-16-15777-2016.
- 631 [25] Castellani V, Piazzalunga A, Sala S. Research findings and decision making: The case of
632 renewable energy. *Environ Sci Eur* 2013;25:1–11. doi:10.1186/2190-4715-25-22.
- 633 [26] Zanetti M, Costa C, Greco R, Grigolato S, Aalmo GO, Cavalli R. How wood fuels' quality
634 relates to the standards: A class-modelling approach. *Energies* 2017;10:1–14.
635 doi:10.3390/en10101455.
- 636 [27] EN ISO 18134-1:2015. Solid biofuels. Determination of moisture content. Oven dry method
637 Part 1: Total moisture — Reference method. Geneva: ISO; 2015.
- 638 [28] EN ISO 18122:2015. Solid biofuels. Determination of ash content. Geneva: ISO; 2015.
- 639 [29] EN ISO 18125:2018. Solid biofuels -- Determination of calorific value. Geneva: ISO; 2018.
- 640 [30] EN ISO 3310-2: 2013. Test sieves. Technical requirements and testing. Part 2: Test sieves of
641 perforated metal plate. Geneva: ISO; 2013.
- 642 [31] EN ISO 17827-1:2016. Solid biofuels. Determination of particle size distribution for
643 uncompressed fuels. Part 1: Oscillating screen method using sieves with apertures of 3,15
644 mm and above. Geneva: ISO; 2016.
- 645 [32] EN ISO 17225-1:2014. Solid biofuel. Fuel specifications and classes. Part 1: General
646 requirements. Norm ISO 17225-1:2014. Geneva: ISO; 2014.

- 647 [33] EN ISO 17225-4:2014. Fuel specifications and classes. Part 4: Graded wood chips. Geneva:
648 ISO; 2014.
- 649 [34] European Committee for Standardization. Stationary source emissions - Determination of
650 low range mass concentration of dust - Manual gravimetric method. EN 13284-1: 2001.
- 651 [35] Giorio C, Tapparo A, Scapellato ML, Carrieri M, Apostoli P, Bartolucci GB. Field
652 comparison of a personal cascade impactor sampler, an optical particle counter and CEN-EU
653 standard methods for PM₁₀, PM_{2.5} and PM₁ measurement in urban environment. J Aerosol
654 Sci 2013;65:111–20. doi:10.1016/j.jaerosci.2013.07.013.
- 655 [36] Laskina O, Morris HS, Grandquist JR, Qin Z, Stone EA, Tivanski A V, et al. Size Matters in
656 the Water Uptake and Hygroscopic Growth of Atmospherically Relevant Multicomponent
657 Aerosol Particles. J Phys Chem A 2015;119:4489–97. doi:10.1021/jp510268p.
- 658 [37] Ente Nazionale Italiano di Unificazione. Emission measurement - Determination of velocity
659 and flow rate in conveyed gas flow by Pitot tube. UNI 10169: 2001.
- 660 [38] European Committee for Standardization. Stationary source emissions - Determination of the
661 mass concentration of PCDDs/PCDFs and dioxin-like PCBs - Part 1: Sampling of
662 PCDDs/PCDFs. EN 1948-1: 2006.
- 663 [39] European Committee for Standardization. Stationary source emissions - Determination of the
664 mass concentration of PCDDs/PCDFs and dioxin-like PCBs - Part 2: Extraction and clean-up
665 of PCDDs/PCDFs. EN 1948-2: 2006.
- 666 [40] Piazza R, Gambaro A, Argiriadis E, Vecchiato M, Zambon S, Cescon P, et al. Development
667 of a method for simultaneous analysis of PCDDs, PCDFs, PCBs, PBDEs, PCNs and PAHs in
668 Antarctic air. Anal Bioanal Chem 2013;405:917–32. doi:10.1007/s00216-012-6464-y.

- [41] Pizzini S, Piazza R, Cozzi G, Barbante C. Simultaneous determination of halogenated contaminants and polycyclic aromatic hydrocarbons: a multi-analyte method applied to filter-feeding edible organisms. *Anal Bioanal Chem* 2016;408:7991–9. doi:10.1007/s00216-016-9897-x.
- [42] Balampanis DE, Coulon F, Simms N, Longhurst P, Pollard SJT, Fenech C, et al. An assessment of different extraction and quantification methods of penta- and hexachlorobenzene from SRF fly-ash. *Anal Chem Res* 2017;12:28–33. doi:10.1016/j.ancr.2017.01.003.
- [43] Kutchko BG, Kim AG. Fly ash characterization by SEM-EDS. *Fuel* 2006;85:2537–44. doi:10.1016/j.fuel.2006.05.016.
- [44] Ranjbar N, Kuenzel C. Cenospheres: A review. *Fuel* 2017;207:1–12. doi:10.1016/j.fuel.2017.06.059.
- [45] Fenelonov VB, Mel'gunov MS, Parmon VN. The properties of cenospheres and the mechanism of their formation during high-temperature coal combustion at thermal power plants. *KONA Powder Part J* 2010;28:189–208. doi:10.14356/kona.2010017.
- [46] Yang JS, Lee SK, Park YH, Lee DW. Analytical method for dioxin and organo-chlorinated compounds: (II) Comparison of extraction methods of dioxins from XAD-2 adsorbent. *Bull Korean Chem Soc* 1999;20:689–95.
- [47] Pizzini S, Marchiori E, Piazza R, Cozzi G, Barbante C. Determination by HRGC/HRMS of PBDE levels in edible Mediterranean bivalves collected from north-western Adriatic coasts. *Microchem J* 2015;121:184–91. doi:10.1016/j.microc.2015.03.010.
- [48] European Committee for Standardization. Stationary source emissions - Determination of the mass concentration of PCDDs/PCDFs and dioxin-like PCBs - Part 3: Identification and

- 692 quantification of PCDDs/PCDFs. EN 1948-3: 2006.
- 693 [49] Badocco D, Lavagnini I, Mondin A, Tapparo A, Pastore P. Limit of detection in the presence
 694 of instrumental and non-instrumental errors: Study of the possible sources of error and
 695 application to the analysis of 41 elements at trace levels by ICP-MS technique. *Spectrochim*
 696 *Acta - Part B At Spectrosc* 2015;107:178–84. doi:10.1016/j.sab.2015.03.009.
- 697 [50] Salcedo RLR, Chibante VG, Fonseca AM, Cândido G. Fine particle capture in biomass
 698 boilers with recirculating gas cyclones: Theory and practice. *Powder Technol* 2007;172:89–
 699 98. doi:10.1016/j.powtec.2006.10.027.
- 700 [51] Khan AA, de Jong W, Jansens PJ, Spliethoff H. Biomass combustion in fluidized bed
 701 boilers: Potential problems and remedies. *Fuel Process Technol* 2009;90:21–50.
 702 doi:10.1016/j.fuproc.2008.07.012.
- 703 [52] Nogales R, Delgado G, Quirantes M, Romero M, Romero E, Molina-Alcaide E.
 704 Characterization of Olive Waste Ashes as Fertilizers. In: Insam H, Knapp B, editors. *Recycl.*
 705 *Biomass Ashes*, Springer, Berlin, Heidelberg; 2011, p. 57–68.
- 706 [53] Haglund N. Guideline for Classification of Ash from Solid Biofuels and Peat Utilised for
 707 Recycling and Fertilizing in Forestry and Agriculture. NT technical 613. Nordic Innovation
 708 Centre, Oslo, Norway. 2008:34. [http://www.nordtest.info/images/documents/nt-technical-](http://www.nordtest.info/images/documents/nt-technical-reports/NT_TR_613_Guideline_for_classification_classification_of_ash_from_solid_biofuels_and_peat_utilised_for_recycling_and_fertilizing_in_forestry_and_agriculture_Nordtest_Technical_Report.pdf)
 709 [reports/NT TR 613_Guideline for classification classification of ash from solid biofuels and](http://www.nordtest.info/images/documents/nt-technical-reports/NT_TR_613_Guideline_for_classification_classification_of_ash_from_solid_biofuels_and_peat_utilised_for_recycling_and_fertilizing_in_forestry_and_agriculture_Nordtest_Technical_Report.pdf)
 710 [peat utilised for recycling and fertilizing in forestry and agriculture_Nordtest Technical](http://www.nordtest.info/images/documents/nt-technical-reports/NT_TR_613_Guideline_for_classification_classification_of_ash_from_solid_biofuels_and_peat_utilised_for_recycling_and_fertilizing_in_forestry_and_agriculture_Nordtest_Technical_Report.pdf)
 711 [Report.pdf](http://www.nordtest.info/images/documents/nt-technical-reports/NT_TR_613_Guideline_for_classification_classification_of_ash_from_solid_biofuels_and_peat_utilised_for_recycling_and_fertilizing_in_forestry_and_agriculture_Nordtest_Technical_Report.pdf) (accessed July 16, 2018).
- 712 [54] Obernberger I, Supancic K. Possibilities of ash utilisation from biomass combustion plants.
 713 *Proceedings of the 17th European Biomass Conference & Exhibition, Hamburg: ETA-*
 714 *Renewable Energies (Ed.); 2009, p. 12.*

- 715 [55] Italian Legislative Decree, D.Lgs. 152/ 2006.
 716 <http://www.camera.it/parlam/leggi/deleghe/06152dl.htm> (accessed July 9, 2018).
- 717 [56] European Committee for Standardization. Heating boilers Part 5 : Heating boilers for solid
 718 fuels , manually and automatically stoked , Terminology , requirements , testing and
 719 marking. EN 303-5: 2012.
- 720 [57] Orasche J, Seidel T, Hartmann H, Schnelle-Kreis J, Chow JC, Ruppert H, et al. Comparison
 721 of emissions from wood combustion. part 1: Emission factors and characteristics from
 722 different small-scale residential heating appliances considering particulate matter and
 723 polycyclic aromatic hydrocarbon (PAH)-related toxicological potential o. *Energy and Fuels*
 724 2012;26:6695–704. doi:10.1021/ef301295k.
- 725 [58] Italian Legislative Decree, D.Lgs. 46/2014, Implementation of the EU Directive 2010/75/EU
 726 n.d. <http://www.governo.it/sites/governo.it/files/74990-9771.pdf> (accessed July 9, 2018).
- 727 [59] Nisbet ICT, LaGoy PK. Toxic equivalency factors (TEFs) for polycyclic aromatic
 728 hydrocarbons (PAHs). *Regul Toxicol Pharmacol* 1992;16:290–300. doi:10.1016/0273-
 729 2300(92)90009-X.
- 730 [60] Samburova V, Zielinska B, Khlystov A. Do 16 Polycyclic Aromatic Hydrocarbons Represent
 731 PAH Air Toxicity? *Toxics* 2017;5:17. doi:10.3390/toxics5030017.
- 732 [61] Van den Berg M, Birnbaum LS, Denison M, De Vito M, Farland W, Feeley M, et al. The
 733 2005 World Health Organization reevaluation of human and mammalian toxic equivalency
 734 factors for dioxins and dioxin-like compounds. *Toxicol Sci* 2006;93:223–41.
 735 doi:10.1093/toxsci/kfl055.

736